

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Low Voltage Cable

with type designation(s)
BFOU (i) S3/S7/S103 & (c) S4/S8/S104 250 V,
BFOU (i&c) 250 V,
BFOU XFR (i) & (c) & (i&c) 250 V,
BFCU XFR (i) & (c) & (i&c) 250 V

Issued to

Draka Norsk Kabel - part of the Prysmian Group
DRAMMEN, Norway

is found to comply with
DNV GL rules for classification – Ships and offshore units

Application :

Control. Instrumentation. Communication. Fire resistant.

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.

Type	Voltage class (V)	Temp. class (°C)
BFOU (i) S3/S7/S103 & (c) S4/S8/S104 250 V	250	90
BFOU (i&c) 250 V	250	90
BFOU XFR (i) & (c) & (i&c) 250 V	150/250	90
BFCU XFR (i) & (c) & (i&c) 250 V	150/250	90

This Certificate is valid until **2021-06-29**.

Issued at **Høvik** on **2016-11-22**

for **DNV GL**

DNV GL local station: **Station Oslo Maritime and CAP**

Approval Engineer: **Ivar Bull**

.....
Andreas Kristoffersen
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

Job Id:
 Certificate No: **TAE000015V**
 Revision No: **5**

Product description

Types: BFOU (i) S3/S7/S103 & (c) S4/S8/S104 250 V,
 BFOU (i&c) 250 V,
 BFOU XFR (i) & (c) & (i&c) 250 V,
 BFCU XFR (i) & (c) & (i&c) 250 V
 On request: Cold bend -40°C / Cold impact -35°C.

Construction:

Conductors: Tinned, stranded copper and Mica-tape helically applied directly over the copper conductor
 Core insulation: EPR
 Inner covering: Extruded flame retardant halogen free compound
 Metal covering: Tinned, Copper wire braid (O) or Galvanized steel wire braid (C)
 Outer sheath: SHF2 mud resistant according to IEC 60092-360 Annex D. NEK TS 606.

BFOU/BFCU and BFOU/BFCU-XFR Collective screen (c):

No of Elements:	Cross sectional area [mm ²]
1, 2, 4, 8, 12, 16, 19, 24 pairs	0,75 1,5 2,5 mm ²
1, 2, 4, 8, 12, 16, 19, 24 triples	0,75 1,5 2,5 mm ²
1 quad	0,75 1,5 2,5 mm ²

BFOU/BFCU and BFOU/BFCU-XFR Individual screen:

No of Elements:	Cross sectional area [mm ²]
1, 2, 4, 8, 12, 16, 24 pairs	0,75 1,5 2,5 mm ²
1, 2, 4, 8, 12, 16, 19, 24 triples	0,75 1,5 2,5 mm ²
1 quad	0,75 1,5 2,5 mm ²

BFOU/BFCU and BFOU/BFCU-XFR Individual & Collective screen:

No of Elements:	Cross sectional area [mm ²]
1, 2, 4, 8, 12, 16, 24 pairs	0,75 1,5 2,5 mm ²
1, 2, 4, 8, 12, 16, 19, 24 triples	0,75 1,5 2,5 mm ²
1 quad	0,75 1,5 2,5 mm ²

Application/Limitation

This type of cable is fire resistant in accordance with IEC Publication 60331.
 The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Tests carried out

Standard	Issued	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-376	2003-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	

Job Id:
 Certificate No: **TAE000015V**
 Revision No: **5**

Standard	Issued	General description	Limitation
IEC 60331-21	1999-04	Tests for electric cables under fire conditions – Circuit integrity – Part 21: Procedures and requirements – Cables of rated voltage up to 0,6/1,0 kV	180 min. test @100 °C + 15 minutes cooling down
IEC 60331-1/2	2009-05	Fire resistance / Circuit integrity – Test for method for fire with shock at temperature of at least 830°C for cables rated up to and including 0,6/1kV	120 minutes @830 °C + 15 minutes cooling down
IEC 60332-1-2	2004-07	Tests on electric and optical fibre cables under fire conditions - Part 1-2: Test for vertical flame propagation for a single insulated wire or cable	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS
IEC 61034-1/2	2005-04	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke
NEK TS606 Ed. 5	2009-05	Cables for offshore installations. Halogen-free and/or mud resistant. Technical specification.	

On special request (-XFR): After Fire test IEC 331-1/2

EN50200 Annex E	2006-05	Method of test for resistance to fire of unprotected small cables for use in emergency circuits. The standard also includes in Annex E a means of applying water spray to the cable during the test.	Water spray for 15 minutes
BS 8491	20008	Method for assessment of fire integrity of large diameter power cables for use as components for smoke and heat control systems and certain other active fire safety systems	Water jet, 12,5 l/min: 5x5sec
		Water submersion	15 min.

Job Id:
Certificate No: **TAE000015V**
Revision No: **5**

On special request: Arctic Grade

IEC 60092-350	2014-08	Annex E: Cold bend test and impact test for low temperature behaviour	Cold bend: -40°C Cold impact: -35°C
CSA C22.2 No.03	2009	4.12 Flexibility at any specified temperature	Cold bend: -40°C
CSA C22.2 No.03	2009	4.13 Abnormal low temperature – impact	Cold impact: -35°C

Marking of product

"meter" "year" "week" "DRAKA 01" "Part no" BFOU (i) S3/S7/S103 or (c) S4/S8/S104 or BFOU (i&c) – ARCTIC GRADE (optional) – XFR (optional) - size – 150/250 V – IEC 60331 – IEC 60332-3-22 – IEC 60092-376 "Prod. Order no"

"meter" "year" "week" "DRAKA 01" "Part no" BFCU (i) or (c) or (i&c) – ARCTIC GRADE (optional) – XFR (optional) – size – 150/250 V – IEC 60331 – IEC 60332-3-22 – IEC 60092-376 "Prod. Order no"

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Assessment to be performed at least every second year.

END OF CERTIFICATE