

Part 1B**Subject: Electrical Equipment (Not Environmentally Tested)****Product: Cables Control, Telecommunication and Instrumentation (Part 1B)**

Producer/Licence No.	Description of Product				Cert. No.
	Type	Details of Approval	Application	Remarks	
Prysmian Group, Draka Norsk Kabel AS, Drammen Norway, Kjerraten 16, Drammen, N-3001, Norway.	FlexFlame RFOU(i) 150/250(300)V RFOU(c) 150/250(300)V	Flame retardant, halogen free, low smoke, twisted pairs/triples signal cable, individually or collectively screened. Insulation: EPR Bedding: Halogen free (<0.5%) elastomer Screening: Polyester tape w/tinned Cu drain wire Outersheath: Halogen free (<0.5%) elastomer SHF2 Conductor size (mm2) No of pairs No of triples 0.75 to 1.5 1 to 24 (32) 1 to 24 2.5 1 to 4 (12) Rated voltage: 250V Maximum conductor temperature: 90°C	Fixed wiring for control, instrumentation and communications on ships, offshore and industrial installations	Expires: 12 September 2016 Flame retardance IEC 60332-1, IEC 60332-3-22 Halogen-free IEC 60754-1, -2 Low smoke IEC 61034-1,-2	12/70022(E5)

© LLOYD'S REGISTER, 2010

NOTICE AND TERMS OF USE

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

<http://www.cdlive.lr.org/information/>