Part 1B
Subject: Electrical Equipment (Not Environmentally Tested)
Product: Cables Power (Part 1B)

Producer / Licence No.	Description of Product				Cert. No.
	Type	Details of Approval	Application	Remarks	
Prysmian Group, Draka Norsk Kabel AS, Drammen Norway, Kjerraten 16, Drammen, N-3001, Norway.	Marine power cabel Type: FlexFlame BFOU 0.6 / 1(1.2) kV Conductor size (mm²) — No of cores 16 to 630 — 1 1.5 to 70 — 2 1.5 to 120 — 3 & 4 1.5, 2.5 & 4 — 5 1.5 & 2.5 — 7, 12, 19, 27 & 37 1.5 — 32 Double braided cables (2-, 3- & 4 core) incl., but not listed above Rated voltage: 0.6 / 1(1.2)kV Maximum conductor temperature: 90°C	Fire resistant, flame retardant, halogen free, low smoke power cable. Insulation:Mica fire resistant tape / EPR Bedding: Halogen free (<0.5%) Elastomer Armour: Tinned copper wire braid Outer sheath:Halogen free (<0.5%) elastomer SHF2	Fixed wiring in ships, offshore and industrial installations Flame retardance IEC 60332-1, IEC 60332-3-22 Fire resistance IEC 60331-1 Halogen-free IEC 60754-1, -2 Smoke emission IEC 61034-1,-2	Expires: 12 September 2016	12 / 70021(E5)

© LLOYD'S REGISTER, 2010

NOTICE AND TERMS OF USE

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.